



1:25

1:50

Tragfähigkeit auf Rädern stehend / Lifting capacity standing on wheels	3500 kg
Tragfähigkeit radfreies Heben / Lifting capacity free hanging wheels	3000 kg
Nutzhub / Effective stroke	840 mm
Auffahrhöhe / Drive-on height	140 mm
Gesamthöhe Mittelstisch minimal / Overall height min.	150 mm + 68mm*
Gesamthöhe maximal / Overall height max.	990 mm + 68mm*
Arbeitshöhe / Work height	ca. 1280 mm
Bühnenmaße inkl. Auffahrrampen (aufgesetzt) und Überfahrsperrern. Dimension if the lift with ramps and overtravel-barriers is on the ground.	4950 mm x 2200 mm
Bühnenmaße ohne Auffahrrampen und Überfahrsperrern. Dimension without ramps or overtravel-barriers.	4230 mm x 2200 mm
Auffahrbreite / Driving width	Ca. 1060 mm - 2100 mm
Luftanschluss max. Druck P <sub>max</sub> / Compressed air supply outlet P <sub>max</sub>	8 bar
Emissionschalldruckpegel L <sub>PA</sub> / Emission sound pressure level L <sub>PA</sub>	70 dB(A)
Antrieb / Propulsion system	Luftfederbalg / double-convolution air spring
Gewicht / Weight	ca. 940 kg

\*Höhe schwenkbarer Tragarme inkl. Schwenkplatten ca. 68mm / Height of supporting arms ca.68mm

(Art.-No.) 10000062	(Allow. dev.)	(Surface)	Scale 1:25	(Weight) ca. 940 kg
			(Material) (Blank dimensions)	
	Date 21.06.22	Name J. Rohmann	(Title) Carry Twin XL - S BJ ab 2022 -Technische Daten / Specifications-	
	Drawn	Checked		
	Appr.			
			(Drawing number) 001.016.100.001	Sheet 1
				1 Pa.
Mark	Revision	Date	Name (Bea.)	(Cr. f.)
				(Cr. by)

COPYING THIS DOCUMENT, DISCLOSING IT TO THIRD PARTIES OR USING THE CONTENTS THERE FOR ANY PURPOSES WITHOUT EXPRESS WRITTEN AUTHORIZATION BY USE IS ILLEGALLY FORBIDDEN. ANY OFFENDERS ARE LIABLE TO PAY ALL RELEVANT DAMAGES.

- Technische Änderungen und Irrtümer vorbehalten / Technical changes and errors reserved -

001.016.100.001

Sheet 1

1 Pa.